

INSERTA TEE® SPECIFICATIONS

SDR26 HWS GASKETED BELL GRAVITY APPLICATIONS

- A.** Bell end accepts pipe with SDR26, ASTM D 3034 or equivalent O.D. specification in 4", 6", 8", 10", 12", 15" and 18" sizes
4" and 6" are new FATBOY® design
- B.** Curvature varies with mainline diameters
- C.** Spigot end PVC SDR26, ASTM D 3034
Diameters: 4", 6", 8", 10", 12", 15" sizes



PART	PART NAME	MATERIALS
1	Hub adaptor	PVC SDR26 ASTM D 3034
2	Rubber Gasket	ASTM F 477
3	Securing Clamp*	Band SS #301 Screw SS #305
4	Rubber Sleeve	Housing SS #301
4A	Upper Segment**	ASTM F 477
4B	Lower Segment***	

- * Optional: #316 Stainless Steel band, screw and housing
- ** Distance between 4A and 4B will vary by product type
- *** Will not appear on rubber sleeves for concrete or clay pipe

INSERTA TEE SIZE	HOLE DIAMETER
4" (100 mm)	4 1/2" (112.5 mm)
6" (150 mm)	6 1/2" (162.5 mm)
8" (200 mm)	8 3/4" (218.8 mm)
10" (250 mm)	10 7/8" (271.9 mm)
12" (300 mm)	12 7/8" (321.8 mm)
15" (375 mm)	15 13/16" (395.3 mm)
18"	19 3/16"

NOTE: Recommended method of cutting hole is with hole saw for PVC and polyethylene, and diamond bit for concretes, clay and D.I. (See Installation Instruction)

INSERTA TEE
 phone 503.357.2110 fax 503.359.5417
 email marty@insertatee.com
www.insertatee.com

