



**INSERTA TEE FITTINGS MEET THE FOLLOWING
ASTM SPECIFICATIONS:**

FIELD PERFORMANCE - C969, F1417, F2487, F2946
WATERTIGHT CONNECTION - D3212 (10.8 psig)
RUBBER SLEEVE AND GASKETS - F477

90 DEGREE ELBOW
 ROOF DRAIN LEADER
 MATERIAL MAY VARY
 (PVC, HDPE, SCH40, ETC.)

EXISTING MAINLINE PIPE, DIAMETER
 AND MATERIAL MAY VARY
 (PVC, HDPE, RCP, DIP, ETC.)

INSERTA TEE CONNECTION
 DESIGNED TO CONNECT 2" (51 mm)
 THROUGH 30" (750 mm) SERVICES
 TO ALL KNOWN SOLID WALL, PROFILE,
 CLOSED PROFILE AND CORRUGATED
 PIPE MANUFACTURED TODAY.



INSERTA TEE | PO BOX 714
 CORNELIUS, OR 97116
 PH:(503) 357-2110 FAX:(503) 359-5417
 SALES@INSERTATEE.COM

INSERTA TEE - ROOF DRAIN LEADER	
SCALE:	NTS
DATE:	7/30/13
DRAWN BY:	JJC

THIS PRINT DISCLOSES SUBJECT MATTER IN WHICH INSERTA-TEE HAS PROPRIETARY RIGHTS. THE RECEIPT OR POSSESSION OF THIS PRINT DOES NOT CONFER, TRANSFER, OR LICENSE THE USE OF THE DESIGN OR TECHNICAL INFORMATION SHOWN HEREIN REPRODUCTION OF THIS PRINT OR ANY INFORMATION CONTAINED HEREIN, OR MANUFACTURE OF ANY ARTICLE HEREFROM, FOR THE DISCLOSURE TO OTHERS IS FORBIDDEN, EXCEPT BY SPECIFIC WRITTEN PERMISSION FROM INSERTA-TEE.

© 2013 INSERTA-TEE