



**INSERTA TEE FITTINGS MEET THE FOLLOWING
ASTM SPECIFICATIONS:**

FIELD PERFORMANCE - C969, F1417, F2487, F2946
WATERTIGHT CONNECTION - D3212 (10.8 psig)
RUBBER SLEEVE AND GASKETS - F477

**INSERTA TEE CONNECTION
DESIGNED TO CONNECT 2" (51 mm)
THROUGH 30" (750 mm) SERVICES
TO ALL KNOWN SOLID WALL, PROFILE,
CLOSED PROFILE AND CORRUGATED
PIPE MANUFACTURED TODAY.**



INSERTA TEE | PO BOX 714
 CORNELIUS, OR 97116
 PH: (503) 357-2110 FAX: (503) 359-5417
 SALES@INSERTATEE.COM

INSERTA TEE - ROOF DRAIN LEADER OPTION 2

SCALE: NTS
 DATE: 9-27-2018
 DRAWN BY: RJ3

THIS PRINT DISCLOSES SUBJECT MATTER IN WHICH INSERTA-TEE HAS PROPRIETARY RIGHTS. THE RECEIPT OR POSSESSION OF THIS PRINT DOES NOT CONFER, TRANSFER, OR LICENSE THE USE OF THE DESIGN OR TECHNICAL INFORMATION SHOWN HEREIN REPRODUCTION OF THIS PRINT OR ANY INFORMATION CONTAINED HEREIN, OR MANUFACTURE OF ANY ARTICLE HEREFROM, FOR THE DISCLOSURE TO OTHERS IS FORBIDDEN, EXCEPT BY SPECIFIC WRITTEN PERMISSION FROM INSERTA-TEE.

© 2013 INSERTA-TEE