

INSERTA TEE® FITS ANY MAINLINE OR STRUCTURE

AIR-TESTABLE, WATERTIGHT* AND VERSATILE

INSERTA TEE is a three-piece service connection consisting of a PVC Hub, Rubber Sleeve and Stainless Steel Band. INSERTA TEE is compression fit into the cored wall of a mainline and requires no special tooling. INSERTA TEES are designed to connect 2" (51 mm) through 30" (750 mm) services to all known solidwall, profile, closed profile and corrugated pipe manufactured today.

INSERTA TEE allows for tapping of existing lines without disturbing the bedding. It eliminates glues, epoxies, grout and awkward gaskets and the need to retighten bands around the mainline.

INSERTA TEE is designed to match the internal radius of any pipe and services can be connected where needed. It allows for easier grading of the mainline. It also greatly reduces costs by reducing labor hours and pipe materials. Hole saws are available for sale for all sizes of INSERTA TEES. The use of installation methods or hole saws not purchased from Inserta Fittings will void the performance warranty of the product.

Applications:

- Sanitary Sewers
- Storm Sewers
- Pipe Bursting (HDPE/PVC)
- Sliplining
- Fold-and-Formed Products
- Cured-In-Place Products
- Manholes
- Wet Wells
- Drainage
- Irrigation
- Catch Basins
- Electrical Vaults

INSERTA TEE fittings for all gravity flow pipe and manholes

Ductile Iron	Spirolite	Ultra Rib™	Pro 21®
Fiberglass	DuroMaxx®	PermaLok®	Polyethylene
PVC	Vylon®	Corrugated Metal	Truss®
Ultra Corr™	N-12®	Solflo® Max	A2000®
GOLDFLO®	Kor-Flo™	Concrete	Clay
Weholite®	Asbestos Cement	HP Storm	SaniTite® HP

*Contact your local sales representative for acceptable watertight applications. Not all applications are standard and some may require additional technical assistance.



Rubber Sleeve



Stainless Steel Band



Gasketed PVC Hub

